

# Whicam Story3 CS

Enjoy Wireless & Auto Focus!

Wireless Autofocus Intraoral Camera with Mouse



-IC-WHT60  
-IC-WHC50  
-IC-MQZ40  
-IC-DZ21

-IC-WHW61  
-IC-HCP31  
-IC-HCN30

-CL-DL10  
-CL-DC20

-CL-AT24

-LS-HM20  
-LS-HMT30

-AL-DF10

# Enjoy Wireless & Auto Focus!

Wireless Autofocus Intraoral Camera with Mouse

## 1 Features of Whicam Story3 CS



### High speed digital wireless

High speed digital wireless provide more clear live image without interruption.



### Auto focus

Real Autofocus function shows clear images.



### HD image

High definition show more detail images.



### Gyro mouse built-in

Useable as a mouse.



### Adjustable head angle

User can use the camera with prefer angle.



### 280° twist head

Easy to get approach anywhere in oral cavity.



### Big capacity battery

Long time use with big capacity battery.



### Software compatibility

Support keyboard short-cut data changing program and twain driver.



### OLED screen

Bright and clear OLED screen indicates various device status.



### Adjustable LED brightness

Can adjust LED brightness to avoid light reflecting.



### 3 Color Impressions

Can change live image color impression (Original, Warm, Cool)



## 2 Wireless receiver

### – USB power operation

It doesn't need other electric power supply.  
The receiver works with USB electric power only.

### – Compact design

Compact receiver saves space.

### – Unlimited receiver channel

Digital wireless type support unlimited channel.  
User can use many receivers with on camera

## 4 Minimum System Requirement

PC system:	2.0 Ghz CPU, 1GB RAM
OS:	Windows XP service pack 2 (Windows XP 64 bit is not supported)
USB port:	USB 2.0

## 3 Specification

Model name	IC-WHT60	
Camera (included head)	Operation voltage	3.7V
	Measurement	Approx. 266 x 31 x 37 mm
	Weight	Approx. 140g
	Resolution	1.3 Mega pixel
	Sensor/Lens type	CMOS / Liquid lens
Charger	Measurement	Approx. 169 x 148 x 89 mm
	Weight	Approx. 170 g
	Operation voltage	5V
Disposable cover	Dimensions	Approx. 32 x 100 mm
	Quantity	Approx. 100 pcs by weight x 2ea
	Raw material	Polyethylene
Adapter	Input voltage	AC 100 ~ 240 V
	Output voltage	DC 5V 2A
	UL number	E333054

## 5 DrsViewer2

Image Viewer included.

